

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 1/7 Revision date: 04/09/2020 Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CHEMICO JOINTING CEMENT

1.2. Relevant identified uses of the substance or mixture and uses advised against : Liquid jointing compound for sealing of joints against leakage of petrol, oils, diesel, hydraulic fluid, paraffin, water, steam and gas joints. Not suitable for use with potable water.

1.3. Details of the supplier of the safety data sheet

Company name: CHEMICO SALES & OVERSEAS LTD

Po Box 12905, Solihull, West Midlands B93 3AY

United Kingdom

Tel: +44 (0)1564 742517

Email: admin@chemico.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1564742517 OFFICE HOURS ONLY

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225

Most important adverse effects: Highly flammable liquid and vapour.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

Hazard pictogram: GHS02: Flame (red diamond enclosing flame)

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: If on skin or hair: Take off immediately all contaminated clothing.

Rinse skin with water .

P370+P378: In case of fire: Use media other than water to extinguish.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 2/7 Revision date: 04/09/2020 Revision No: 9

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

Hazardous Ingredient	EINECS	CAS	PBT/WEL	CLP CLASSIFICATION	%
EHTANOL	200-578-6	64-17-5	Substance with a community workplace exposure limit	Flam Liq 2: H225	36.34
METHANOL	200-659-6	67-56-1	-	Flam Liq 2: H2225, Acute Tox 3:H331, Acute Tox 3: H311, Acute Tox 3 H301, STOT SE 1:H370	1.89

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 3/7 Revision date: 04/09/2020 Revision No: 9

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel containers. Do NOT store in lead, zinc, tin or aluminium.

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 4/7 Revision date: 04/09/2020 Revision No: 9

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust:

Hazardous Ingredient	Country/State	Respirable dust:			
		8 hour TWA	15 min STEL	8 hour TWA	15 min STEL
Ethanol	UK	1940 mg/m ³	-	-	-
Methanol	UK	266 mg/m ³	333mg/m ³	-	-

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Refer to specific Country/ State legislation for requirements under Community environmental legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Brown.

Odour: Alcoholic

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Partially miscible.

Also soluble in: Ethanol. Methanol.

Viscosity: Viscous

Boiling point/range°C: 78

Flammability limits %: lower: No data available.

Flash point°C: <23

Auto-flammability°C: No data available.

Melting point/range°C: No data available.

upper: No data available.

Part.coeff. n-octanol/water: No data available.

Vapour pressure: No data available.

Relative density: 0.98 @ 20 C pH: Approx. 7

VOC g/l: No data available.

9.2. Other information : No data available.

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 5/7 Revision date: 04/09/2020 Revision No: 9

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Toxicity values: No data available.

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 6/7 Revision date: 04/09/2020 Revision No: 9

Symptoms / routes of exposure

Skin contact: Possible mild irritation at the site of contact.

Eye contact: Possible irritation and redness.

Ingestion: Possible irritation of the throat.

Inhalation: Possible feeling of tightness in the chest with shortness of breath.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.
(vapour pressure at 50°C more than 110 kPa)
(ETHANOL; METHANOL)

14.3. Transport hazard class

Transport class: 3

14.4. Packing group

Packing group: II limited quantity

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

SAFETY DATA SHEET

Chemico Jointing Cement

Page: 7/7 Revision date: 04/09/2020 Revision No: 9

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H331: Toxic if inhaled.

H370: Causes damage to organs.

Legal disclaimer: The above information in this SDS is believed to be correct but does not purport to be all inclusive and shall be used only as a guide . Chemico Sales & Overseas Limited does not assume responsibility for any results obtained by persons over whose methods Chemico Sales & Overseas Limited has no control. It is the user's responsibility to determine the suitability of this Chemico product or any production methods mentioned herein for a particular purpose and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Chemico Sales & Overseas Limited products. In light of the foregoing, Chemico Sales & Overseas Limited specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Chemico Sales & Overseas Limited products. Chemico Sales & Overseas Limited further disclaims any liability for consequential or incidental damages of any kind, including lost profits.